



Prism Synergy 24V

DIMENSIONS L x W x H

Micro.....	26 x 8.9 x 9.4mm
Mini.....	52.1 x 18.5 x 9.7mm
Spec.....	96 x 18.5 x 9.7mm

BEAM ANGLE.....170°

MOUNTING OPTIONS.....3M Self-adhesive Tape

OPERATING TEMP.....-40° ~ +70°C

ENVIRONMENT.....IP67

WARRANTY.....Life of Sign Warranty



WHITES	COLOUR	POWER	INTENSITY	EFFICIACY	MAX SERIES	LIGHTSPACE	PACKAGING
Prism Synergy Micro	3000k 6500k	0.286W (24V)	46.7 lm/mod	163 lm/W	60 modules per series	30-50mm	Modules per bag: 60 Modules per strand: 60
Prism Synergy Mini	3000k 4100k 5000k 6500k	0.461W (24V)	72.0 lm/mod	156 lm/W	50 modules per series	50-100mm	Modules per bag: 50 Modules per strand: 50
Prism Synergy Spec	3000k 4100k 5000k 6500k	0.888W (24V)	138.4 lm/mod	156 lm/W	50 modules per series	100mm+	Modules per bag: 50 Modules per strand: 50

COLOURS	COLOUR	POWER	INTENSITY	EFFICIACY	MAX SERIES	LIGHTSPACE	PACKAGING
Prism Synergy Mini	Red Green Blue	0.461W (24V)	16.3 lm/mod 43.9 lm/mod 9.8 lm/mod	35 lm/W 95 lm/W 21 lm/W	50 modules per series	60-90mm	Modules per bag: 50 Modules per strand: 50
Prism Synergy Spec	Red Green Blue	0.888W (24V)	20.4 lm/mod 54.9 lm/mod 11.9 lm/mod	23 lm/W 62 lm/W 13 lm/W	50 modules per series	100-150mm	Modules per bag: 50 Modules per strand: 50



Sales & Support

PH 02 9517 3222 | E sales@bounced.com.au
www.bounced.com



Proudly distributed by

BOUNCE LED