








# Bounce LED Cable

Our premium range of LED Cable can be used in all low voltage installations.

| LED CABLE                                                                          |                                                                                                                                                                                                 |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>LED Cable 20AWG - Clear</b><br>Light gauge figure-8 cable. 0.81mm conductor diameter.<br>Clear outer casing. <b>50m roll</b>                                                                 |
|    | <b>LED Cable 18AWG - Red/White</b><br>Regular gauge figure-8 cable. 1.02mm conductor diameter.<br>Red & white casing. <b>100m Roll</b>                                                          |
|    | <b>LED Cable 18AWG - Red/White + PVC</b><br>Regular gauge figure-8 cable. 1.02mm conductor diameter.<br>Red & white casing. Black flexible PVC outer jacket. <b>50m Roll</b>                    |
|   | <b>LED Cable 16AWG - Red/White</b><br>Regular gauge figure-8 cable. 1.29mm conductor diameter.<br>Red & white casing. <b>100m Roll</b>                                                          |
|  | <b>LED Cable 16AWG - Red/White + PVC</b><br>Regular gauge figure-8 cable. 1.29mm conductor diameter.<br>Red & white casing. Black flexible PVC outer jacket. <b>50m Roll</b>                    |
|  | <b>LED Cable 14AWG - Red/White</b><br>Heavy gauge insulated Cable. 1.63mm conductor diameter.<br>Red & white casing. <b>50m roll</b>                                                            |
|  | <b>RGB Cable 20AWG</b><br>Flexible, 4-pin Cable for wiring RGB modules. 0.81mm conductor diameter.<br>Red, green, blue and white casing. <b>20m roll</b>                                        |
|  | <b>RGB Cable 20AWG + PVC</b><br>Flexible, 4-pin Cable for wiring RGB modules. 0.81mm conductor diameter.<br>Red, green, blue and white casing. Black flexible PVC outer jacket. <b>50m roll</b> |
|  | <b>RGBW Cable 20AWG</b><br>Flexible, 5-pin Cable for wiring RGBW modules. 0.81mm conductor diameter.<br>Red, green, blue, white and yellow casing. <b>20m roll</b>                              |

Sales & Support

PH 02 9517 3222 | E [sales@bounced.com.au](mailto:sales@bounced.com.au)  
[www.bounced.com](http://www.bounced.com)

